



EMERGENCY LOCATOR TRANSMITTER

ELT 1000

The ARTEX ELT 1000 is a value-priced upgrade to standard 121.5 MHz transmitters, which are no longer monitored by the Cospas-Sarsat system. The 406 MHz transmitter produces a much more accurate position, typically 3 kilometers as compared with 15 to 20 kilometers for 121.5 MHz transmitters. When coupled to the aircraft navigation system via a built-in navigation interface, the ELT 1000's accuracy improves to approximately 100 meters.



An ACR Electronics Brand



ELT 1000

EMERGENCY LOCATOR TRANSMITTER

Improved Positional Accuracy

The ARTEX ELT 1000 is a value-priced upgrade to standard 121.5 MHz transmitters, which are no longer monitored by the Cospas-Sarsat system. The 406 MHz transmitter produces a much more accurate position, typically 1.86 miles as compared with 9.3 to 12.4 miles for 121.5 MHz transmitters. When coupled to the aircraft navigation system via the built-in GPS interface, the ELT 1000's accuracy improves up to approximately 110 yards.

An Affordable Upgrade

Because it is a single output ELT, the ARTEX ELT 1000 utilizes the same RF output and only one coax cable to transmit a 406 MHz emergency signal to Cospas-Sarsat satellites and a local 121.5 homing signal. The all new built in GPS Nav Interface does not require aircraft power to operate - greatly reducing installation cost. The new remote switch only requires 2-wires, this makes upgrading your older 121.5 MHz ELT simple and affordable



406 MHz



Worldwide Coverage



Integrated GPS NAV Interface



6-Year Lithium LiMnO₂



Easy Installation



Local Search & Rescue



SPECIFICATIONS

Product Number: 8202

Operating Frequencies

121.5 MHz +/-5 KHz
(Emissions Designator 3K20A3X)
406.0 to 406.1 MHz
(Emissions Designator 16K0G1D)

Output Power

406 MHz: SW for 24 hours @ -20°C to +55°C (-4°F -131°F)
121.5 MHz: 100 mW min >50 hours @ -20°C to +55°C (-4°F - 131°F)

Output Connector

BNC Female

Battery

6-year Lithium LiMnO₂

Remote Control

On/Arm/Test

Weights (with tray)

Total Weight: 2.2 lbs (996 g)

Mounting Hardware

ELT 1000 Mounting Tray: 8303

Temperature Certified to:

Operating: -20°C - +55°C (-4°F to +131°F)
Storage: -55°C - 85°C (-67°C to +185°C)

Self-Test Checks

G-Switch Enabled
406 MHz
Antenna/Coax Connection
Low Battery

Measurements

ELT Transmitter with mounting hardware installed:
6.59" (L) x 2.86" (H) x 3.69" (W) inches
(167x 73 x 94 mm)

Other Parts

Coax Cable and Antenna
Audio Buzzer (alert ground crews of inadvertent activations)
Remote Switch
ACE Adapter Module
(Optional for ACK retrofit)

Certifications

- TSO C126B
- TSO C142A
- ETSO C126a, C142a
- Cospas-Sarsat
- Industry Canada
- Brazil ANAC & ANATEL
- Japan JCAB & JTAB

Activation Method

Automatic by 4.5 ft/sec (2.3 G) Primary G-Switch and Manual Activation

	ELT KIT	SWITCHES	ANTENNAS
ELT 1000	8202	N/A	N/A
	8203	8304	110-773
	8204	8304	110-338 or 110-338-01
	8205	453-0023	110-773
	8206	453-0023	110-773



ACE
M/N
453-0023



Standard
M/N
A3-06-2759



121.5/406 MHz
M/N
110-773



Tri-Band
M/N
110-338
or
110-338-01

For further information please contact:

ACR Electronics, Inc.
5757 Ravenswood Road
Fort Lauderdale, FL 33312

www.ACRARTEX.com

Tel: (954) 981.3333
Fax: (954) 983.5087
Email: sales@acrartex.com

This document is the property of ACR Electronics, Inc. (ACR) and is distributed by ACR for the benefit of our customers. This document may not be disseminated, reproduced or altered in any way without the prior written approval of ACR Electronics, Inc.